COMPRESSOR DATA SHEET

Rotary Compressor: Variable Frequency Drive

	MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer: Boge Kompressoren			
2	Model Number: C 16 F	Date:	5/15/2019	
	X Air-cooled Water-cooled	Type:	Screw	
	X Oil-injected Oil-free	# of Stages:	Single	
3	Rated Operating Pressure	105	psig ^b	
4	Drive Motor Nominal Rating	15	hp	
5	Drive Motor Nominal Efficiency	91.9	percent	
6	Fan Motor Nominal Rating (if applicable)	0.8	hp	
7	Fan Motor Nominal Efficiency	78.0	percent	
8*	Input Power (kW)	Capacity (acfm) ^{a,d}	Specific Power (kW/100 acfm) ^d	
	13.8 Max	69.2	19.94	
	11.5	57.6	19.98	
	9.5	45.2	21.02	
	7.5	32.8	22.84	
	Min	18.7		
9*	Total Package Input Power at Zero Flow ^{c, d}		0	
10	35.00 30.00 30.00 25.00 15.00 10.00 10.00 25.0 Capa	50.0 city (ACFM) representation of the data in Sective (V100acfm increments if necessary)		

*For models that are tested in the CAGI Performance Verification Program, these items are verified by program administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

NOTES:


a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; acfin is actual cubic feet per minute at inlet conditions.

Mambar

Compressed Air & Gas Institute

- b. The operating pressure at which the Capacity and Electrical Consumption were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.



ROT 031

This form was developed by the Compressed Air and Gas Institute for the use of its members. CAGI has not independently verified the reported data.