COMPRESSOR DATA SHEET

In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

Rotary Compressor: Variable Frequency Drive

		MOI	DEL DA	TA -	FOF	R CO	MPR	ESSI	ED A	IR					
1	Manufacturer:	BOGE													
	Model Number	r: SLF 6	1-3							Da	te:	2	4.11.202	1	
2	X Air-cooled Water-cooled									Тур	oe:		Screw		
									# o	f Stage	es:		1		
3*	Full Load Ope	rating Pressu	re ^b				115						psig		
4	Drive Motor N						60						hp		
5	Drive Motor Nominal Efficiency						94			percent					
6	Fan Motor Nominal Rating (if applicable)						3,5			hp					
7	Fan Motor No	Fan Motor Nominal Efficiency					86,5			percent					
	Input Power (kW)					Capac	ity (ac	efm) ^{a,o}	ı	Specific Power (kW/100 acfm) ^d					
					278,9				19,77						
8*					239,4				20,20						
	42,6					205,9			20,67						
	37,5					176,2			21,28						
		25,6				109,5 23,38					38				
9*	Total Package	Total Package Input Power at Zero Flow c, d					0,0			kW					
10	Isentropic Effic	ciency				•	68,0%	D	%						
11	Specific Power (kW/100 ACFM)		5,0 50,0 Note: Gra ote: Y-Axis S	cale, 10 to	y a visual o 35, + 5k		tation of	nents if n	ecessary a		250,0	275,0	300,0		

*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator Consult CAGI website for a list of participants in the third party verification program: www.cagi.org



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E;
 ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:

NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Member

	olume Flow Rate pecified conditions	Volume Flow Rate	Specific Energy Consumption	Zero Flow Power	
$\underline{m}^3 / \underline{min}$	ft ³ / min	%	%	%	
Below 0.5	Below 17.6	+/- 7	+/- 8		
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%	
1.5 to 15	53 to 529.7	+/- 5	+/- 6		
Above 15	Above 529.7	+/- 4	+/- 5		

ROT 031.1