## **COMPRESSOR DATA SHEET**

In Accordance with Federal Uniform Test Method for Certain Lubricated Air Compressors

**Rotary Compressor: Fixed Speed MODEL DATA - FOR COMPRESSED AIR** Manufacturer: 1 **BOGE Compressor** S 111-4 N 21.07.2022 Model Number: Date: 2 Air-cooled Water-cooled x Screw Type: 1 # of Stages: Rated Capacity at Full Load Operating Pressure a, e acfm<sup>a,e</sup> 3\* 684 Full Load Operating Pressure b psig 4\* 110 Maximum Full Flow Operating Pressure psig 5 125 Drive Motor Nominal Rating 150 6 hp Drive Motor Nominal Efficiency 7 96,2 percent Fan Motor Nominal Rating (if applicable) 8 4 hp Fan Motor Nominal Efficiency 9 89,5 percent Total Package Input Power at Zero Flow<sup>e</sup>  $kW^e$ 10\* 20,2 Total Package Input Power at Rated Capacity and Full Load  $kW^{d} \\$ 11 116,78 Operating Pressure<sup>d</sup> Package Specific Power at Rated Capacity and Full Load Operating 12\* 17.08 kW/100 cfm<sup>e</sup> Pressure Isentropic Efficiency 82,02 Percent 13 \*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator.

Consult CAGI website for a list of participants in the third party verification program: www.cagi.org

- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex C; ACFM is actual cubic feet per minute at inlet conditions.
  b. The operating pressure at which the Capacity (Item 3) and Electrical Consumption (Item 11) were measured



NOTES:

- for this data sheet. c. Maximum pressure attainable at full flow, usually the unload pressure setting for load/no load control or the
- maximum pressure attainable before capacity control begins. May require additional power.
  d. Total package input power at other than reported operating points will vary with control strategy.
  e. Tolerance is specified in ISO 1217, Annex C, as shown in table below:



ROT 030.1

ssed kir & (ss institute ) NOTE: The terms "power" and "energy" are synonymous for purposes of this document.					
o Load / Zero Flow Power	Specific Energy Consumption	Volume Flow Rate	Volume Flow Rate at specified conditions		
%	%	%	<u>ft<sup>3</sup> / min</u>	m <sup>3</sup> /min	Member
+/- 10%	+/- 8	+/- 7	Below 17.6	Below 0.5	
	+/- 7	+/- 6	17.6 to 53	0.5 to 1.5	
	+/- 6	+/- 5	53 to 529.7	1.5 to 15	
	+/- 5	+/- 4	Above 529.7	Above 15	Г 030.1
	+/- 8 +/- 7 +/- 6	+/- 7 +/- 6 +/- 5	Below 17.6 17.6 to 53 53 to 529.7	Below 0.5 0.5 to 1.5 1.5 to 15	

12/19 Rev (This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.