## **COMPRESSOR DATA SHEET**

## In Accordance With Federal Uniform Test Method for Certain Lubricated Air Compressors

## **Rotary Compressor: Variable Frequency Drive**

## MODEL DATA - FOR COMPRESSED AIR

	Model Number:	S 75-4 LF N		Date:	29.11.2022
2	X Air-cooled Water-cooled			Type:	Screw
				# of Stages:	1
*	Full Load Operating Pressure <sup>b</sup>		100	psig <sup>b</sup>	
Ļ	Drive Motor Nominal Rating		100	hp	
5	Drive Motor Nominal Efficiency		96	percent	
5	Fan Motor Nominal Rating (if applicable)		3,5	hp	
7	Fan Motor Nominal Efficiency		89,5	percent	
	Input Power (kW)		Capacity (acfm) <sup>a,d</sup>	Specific Power (kW/100 acfm) <sup>d</sup>	
		80,8	478,1	16,	
*	48,9		277,2	17,64	
	34,1		180,8	18,83	
	26,8		132,1	20,26	
	19,9		83,7	.7 23,83	
*	Total Package Input Power at Zero Flow <sup>c, d</sup>		0,0		kW
0	Isentropic Efficiency		76,5%	%	
	35,00				
	30,00				
	25,00 225,00 20,000 20,00 20,00 20,00 20,00 20,00 20,00 20,00 20,00 20,00 20,00 20,0				
1	Specifi Specifi (KM/10 20,00				

Capacity (ACFM)

Note: Graph is only a visual representation of the data in Section 8 Note: Y-Axis Scale, 10 to 35, + 5kW/100acfm increments if necessary above 35 X-Axis Scale, 0 to 25% over maximum capacity

\*For models that are tested in the CAGI Performance Verification Program, these items are verified by the third party administrator

Consult CAGI website for a list of participants in the third party verification program: <u>www.cagi.org</u>



- a. Measured at the discharge terminal point of the compressor package in accordance with ISO 1217, Annex E; ACFM is actual cubic feet per minute at inlet conditions.
- b. The operating pressure at which the Capacity (Item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power. In accordance with ISO 1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO 1217, Annex E, as shown in table below:
  - NOTE: The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions		Volume Flow Rate	Specific Energy Consumption	Zero Flow Power
$\underline{m}^3 / \underline{min}$	$\underline{ft^3} / \underline{min}$	%	%	%
Below 0.5	Below 17.6	+/- 7	+/- 8	
0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	+/- 10%
1.5 to 15	53 to 529.7	+/- 5	+/- 6	
Above 15	Above 529.7	+/- 4	+/- 5	

ROT 031.1

12/19 Rev 3 This form was developed by the Compressed Air and Gas Institute for the use of its members participating in the PVP. CAGI has not independently verified the reported data.