		Rotary Compressor: Fixed Sp MODEL DATA - FOR COMPRES			٦
1	Manufacturer:	BOGE Compressor			-
	Model Number: C 15L N		Date:	10/13/2020	-
2	X Air-cooled Water-cooled		Type:	Screw	-
			# of Stages:	1	-
2*	Pated Capacity at Full Lo	ad Operating Pressure ^{a, e}	67	a,e	_
3*		Capacity at Full Load Operating Pressure ^{a, e}		acfm ^{a,e}	-
4*			135	psig ^b	_
5	Maximum Full Flow Operating Pressure ^c		150	psig ^c	
6	Drive Motor Nominal Rating		15	hp	
7	Drive Motor Nominal Effi	Drive Motor Nominal Efficiency		percent	
8	Fan Motor Nominal Ratin	n Motor Nominal Rating (if applicable)		hp	
9	Fan Motor Nominal Effici	Motor Nominal Efficiency		percent	-
	e		~	kW ^e	_
	Total Package Input Power at Rated Capacity and Full Load		3.1		_
11	Operating Pressure ^d			kW^d	
12*	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		22.36	kW/100 cfm ^e	
					-
13	Isentropic Efficiency	70.00	Percent		
		Performance Verification Program, these items are		ministrator.	
NOTES	S: a. Measured at the disch ISO 1217, Annex C; A	ipants in the third party verification program: arge terminal point of the compressor package in accord ACFM is actual cubic feet per minute at inlet conditions e at which the Capacity (Item 3) and Electrical Consum			
AG Air & Gas Institute	 c. Maximum pressure at maximum pressure att d. Total package input p e. Tolerance is specified 	tainable at full flow, usually the unload pressure setting tainable before capacity control begins. May require ad- ower at other than reported operating points will vary w in ISO 1217, Annex C, as shown in table below: ower" and "energy" are synonymous for purposes of this	ditional power. ith control strategy.		
אוו מ עם וואנונענפ		Volume Flow Rate		Specific Energy	No Load /
ember	$\frac{m^3}{\min}$	at specified conditions $\frac{ft^3 / min}{ft^3}$	Volume Flow Rate %	Consumption %	Pov %
	Below 0.5	Below 17.6	+/- 7	+/- 8	/
	0.5 to 1.5	17.6 to 53	+/- 6	+/- 7	1.7
	1.5 to 15	53 to 529.7	+/- 5	+/- 6	+/-